



GOM-802




FEATURES

- * 30000 Counts Display
- * High Accuracy 0.05%
- * Hi/Lo Comparator and Limit Percent Setting
- * Measurement of REL, Actual and % Value
- * Continuous or Triggered Measurement Mode
- * Temperature Compensation and Measurement
- * Four-Terminal Measurement Technique
- * Auto-Recall Last Setting Before Power OFF
- * Alarm Setting for PASS/FAIL
- * Scan, Handler Interface (Standard)
- * Manual or Autoranging
- * RS-232C+GPIB (Option)

GTL-108A Test Lead

For: GOM-801H/802, GDM-8255A/8251A



PT-100 Temperature Probe

For: GOM-802



Rear Panel



The GOM-802 milliohm meter is designed for component and material impedance measurements in laboratories and other test environments. A large display with 30,000 counts and a superb accuracy of up to 0.05% gives the reliability and flexibility required in demanding measurement applications. Features such as Auto ranging, a built-in comparator offering Hi-Lo testing, a Limit Percent setting, and Go/NoGo testing reduce the effort for complex testing setups. Displayed selections of Relative, Actual, and % Value show results viewed from multiple perspectives. The GOM-802 supports 4 Wire Kelvin resistance measurements for faster accurate results. For an accurate, sophisticated, affordable milliohm meter, the GOM-802 is the right choice.

SPECIFICATIONS

DISPLAY	
Counts	30,000 counts
RESISTANCE	
Ranges/Test Current (Fixed)	30mΩ /1A 300mΩ/100mA 3Ω/100mA
	30Ω /10mA 300Ω/1mA 3kΩ/100μA
	30kΩ /100μA 300kΩ/10μA 3MΩ/1μA
Accuracy	30mΩ: ±0.1% reading + 6 digits 300mΩ: ±0.05% reading + 6 digits 3Ω: ±0.05% reading + 3 digits 30Ω-3MΩ: ±0.05% reading + 2 digits
Resolution	1 μΩ, 10 μΩ, 100 μΩ, 1mΩ, 10mΩ, 100mΩ, 1Ω, 10Ω, 100Ω
TEMPERATURE	
Ranges	-50 °C – 100 °C
Accuracy	-10 °C – 40 °C : 0.3% + 0.5 °C other : 0.3% + 1.0 °C
Resolution	0.1 °C
FUNCTION	
Function	Hi/Lo, Go/No-Go, Manual Trigger, Actual, %, Diode, Temp, TC for Transformer
MEASURING RATE	
Measuring Rate	7 measuring / sec at 30,000 counts, 30 measuring / sec at 3,000 counts
MEMORY	
Memory	20 sets
INTERFACE	
Interface	Standard : Handler / Scan (same connector) Option : RS-232C+GPIB
POWER SOURCE	
Power Source	AC 100/120/220/230V ±10%, 50/60Hz
DIMENSIONS & WEIGHT	
Dimensions & Weight	251 (W) x 91 (H) x 291 (D)mm, Approx. 3kg

ORDERING INFORMATION

GOM-802 High Precision Programmable DC Milli-Ohm Meter

ACCESSORIES :

User manual x 1, Power cord x 1, Test lead GTL-108A x 1

OPTION

Opt.01 RS-232C + GPIB Interface (Factory Installed)

OPTIONAL ACCESSORIES

PT-100 Platinum Temperature Probe

GTL-232 RS232C Cable, 9-pin Female to 9-pin, null Modem for Computer

FREE DOWNLOAD

Driver LabView Driver

Distributed by:
www.SignalTestInc.com <http://www.SignalTestInc.com>
1529 Santiago Ridge Way
San Diego, CA 92154 USA.
Sales@SignalTestInc.com

SIGNAL TEST
New & Used Test Equipment